



Residential LFP Battery Series

W10-5A

51.20V 200Ah 10.240kWh

Version: V1.0



The W10 - 5A is a solar lithium battery for home use. Its intelligent Battery Management System (BMS) can monitor and optimize battery performance in real - time, extend its service life, and enable remote control via a mobile app, making it convenient for you to track your home's energy situation. It is easy to install, and the wall - mounted design saves space. In case of an emergency, it can serve as a power bank to supply power to home appliances, adapting to various scenarios.

FEATURES



Multi-Scenario

- With optional detachable wheels, the battery also offers mobile energy storage functionality
- IP65 protection rating for all-weather use



Longer Life and Safer

- A+ grade lithium iron phosphate
- Built-in hot aerosol fire extinguishing device



Low Maintenance

- Firmware update service via built-in BLE
- Check battery operation status and configure BMS via BLE



Flexible and Expandable

- Up to 20 units in parallel
- The parallel system's max capacity is 204kWh



Certification

- UN38.3, MSDS, TCAR, CB, CE-EMC

Dimensions



Product Name		W10-5A
Electrical Characteristics		
Nominal Voltage	512V	
Nominal Capacity	200Ah	
Energy	10240Wh	
Battery Chemistry	Lithium Iron Phosphate (LFP)	
Cycle Life	8000cycles@80%DOD, 25°C/0.5C	
Operating Voltage	44.8~57.6V	
Communication Interfaces	CAN/RS485/RS232	
Scalable	Up to 20units	
Expansion function	Single-pack level heat aerosol fire extinguishing device / Heating function / Bluetooth / Wheels (optional)	
Charge & Discharge		
Recommended charging/discharging current	100A	
Maximum continuous charge/discharge current	200A	
Recommended charging/discharging current	250A 10S	
Conversion efficiency	99% , 25°C/0.5C	
Environmental		
Environment	Indoors/under the outdoor eaves	
Charging Temperature	With heating function: -20~55°C ; Without heating function: 0~55°C	
Discharging Temperature	-20 to 60 °C	
Storage Temperature	Between 20°C and 45°C within three months; 25 ± 3°C for more than three months	
Storage humidity	65±20%RH	
Altitude	≤3,000 m	
Cooling Method	Natural Convection	
IP Rating	IP65	
Mechanical		
Dimension(L*W*D)	820*494*145mm (excluding wheels)	
Weight	90kg (excluding wheels)	
Installation	Wall mount or floor	
Certification		
UN38.3, MSDS, TCAR, CB, CE-EMC		

*The actual product may have slight differences from some promotional videos or pictures. Please refer to the actual product. Unless otherwise specified the data on this page are all from our company's laboratory. The data may have errors due to changes in the objective environment.

*The specifications are subject to change without prior notice.